



# INTEL® ARRIA® 10 PRODUCT TABLE

PRODUCT LINE		GX 160 SX 160	GX 220 SX 220	GX 270 SX 270	GX 320 SX 320	GX 480 SX 480	GX 570 SX 570	GX 660 SX 660	GX 900	GX 1150	GT 900	GT 1150	
Resources	LEs (K)	160	220	270	320	480	570	660	900	1,150	900	1,150	
	System logic elements (K)	210	288	354	419	629	747	865	1,180	1,506	1,180	1,506	
	Adaptive logic modules (ALMs)	61,510	83,730	101,620	118,730	181,790	217,080	250,540	339,620	427,200	339,620	427,200	
	Registers	246,040	334,920	406,480	474,920	727,160	868,320	1,002,160	1,358,480	1,708,800	1,358,480	1,708,800	
	M20K memory blocks	440	588	750	891	1,438	1,800	2,133	2,423	2,713	2,423	2,713	
	M20K memory (Mb)	9	11	15	17	28	35	42	47	53	47	53	
	MLAB memory (Mb)	1.0	1.8	2.4	2.8	4.3	5.0	5.7	9.2	12.7	9.2	12.7	
	Hardened single-precision floating-point multipliers/adders	156/156	191/191	830/830	985/985	1,368/1,368	1,523/1,523	1,688/1,688	1,518/1,518	1,518/1,518	1,518/1,518	1,518/1,518	
	18 x 19 multipliers	312	382	1,660	1,970	2,736	3,046	3,376	3,036	3,036	3,036	3,036	
	Peak fixed-point performance (GMACS) <sup>1</sup>	343	420	1,826	2,167	3,010	3,351	3,714	3,340	3,340	3,340	3,340	
Peak floating-point performance (GFLOPS)	140	172	747	887	1,231	1,371	1,519	1,366	1,366	1,366	1,366		
Clocks, Maximum I/O Pins, and Architectural Features	Global clock networks	32	32	32	32	32	32	32	32	32	32	32	
	Regional clocks	8	8	8	8	8	8	16	16	16	16	16	
	Hard processor system (available in SX devices only)	Dual-core Arm® Cortex®-A9 MPCore® processor. See the following page for details.								-			
	Maximum LVDS channels (1.6 G)	120	120	168	168	222	324	270	384	384	312	312	
	Maximum user I/O pins	288	288	384	384	492	696	696	768	768	624	624	
	Transceiver count (17.4 Gbps)	12	12	24	24	36	48	48	96	96	72	72	
	Transceiver count (25.78 Gbps)	-	-	-	-	-	-	-	-	-	-	6	6
	PCIe® hardened IP blocks (Gen3 x8) <sup>2</sup>	1	1	2	2	2	2	2	4	4	4	4	
	Maximum 3 V I/O pins	48	48	48	48	48	96	96	-	-	-	-	

Package Options<sup>3</sup> and I/O Pins<sup>4</sup>: General-Purpose I/O (GPIO) Count, High-Voltage I/O Count, LVDS Pairs<sup>5</sup>, and Transceiver Count

U19	U484 pin (19 mm)	192, 48, 72, 6	192, 48, 72, 6	-	-	-	-	-	-	-	-	-
F27	F672 pin (27 mm)	240, 48, 96, 12	240, 48, 96, 12	240, 48, 96, 12	240, 48, 96, 12	-	-	-	-	-	-	-
F29	F780 pin (29 mm)	288, 48, 120, 12	288, 48, 120, 12	360, 48, 156, 12	360, 48, 156, 12	360, 48, 156, 12	-	-	-	-	-	-
F34	F1152 pin (35 mm)	-	-	384, 48, 168, 24	384, 48, 168, 24	492, 48, 222, 24	492, 48, 222, 24	492, 48, 222, 24	504, 0, 252, 24	504, 0, 252, 24	-	-
F35	F1152 pin (35 mm)	-	-	384, 48, 168, 24	384, 48, 168, 24	396, 48, 174, 36	396, 48, 174, 36	396, 48, 174, 36	-	-	-	-
KF40	F1517 pin (40 mm)	-	-	-	-	-	696, 96, 324, 36	696, 96, 324, 36	-	-	-	-
NF40	F1517 pin (40 mm)	-	-	-	-	-	588, 48, 270, 48	588, 48, 270, 48	600, 0, 300, 48	600, 0, 300, 48	-	-
RF40	F1517 pin (40 mm)	-	-	-	-	-	-	-	342, 0, 154, 66	342, 0, 154, 66	-	-
NF45	F1932 pin (45 mm)	-	-	-	-	-	-	-	768, 0, 384, 48	768, 0, 384, 48	-	-
SF45	F1932 pin (45 mm)	-	-	-	-	-	-	-	624, 0, 312, 72	624, 0, 312, 72	624, 0, 312, 72	624, 0, 312, 72
UF45	F1932 pin (45 mm)	-	-	-	-	-	-	-	480, 0, 240, 96	480, 0, 240, 96	-	-

Notes:

- Fixed-point performance assumes the use of pre-adder.
- Certain packages might not bond out all PCIe hard IP blocks.
- All packages are ball grid arrays with 1.0 mm pitch, except for U19 (U484), which is 0.8 mm pitch.
- A subset of pins for each package are used for 3.3 V and 2.5 V interfaces.
- Each LVDS pair can be configured as either a differential input or a differential output.
- All data is correct at the time of printing, and may be subject to change without prior notice. For the latest information, please visit [www.altera.com](http://www.altera.com).

192, 48, 72, 6 Numbers indicate GPIO count, high-voltage I/O count, LVDS pairs, and transceiver count.  
 Indicates pin migration.



# INTEL ARRIA 10 PRODUCT TABLE

PRODUCT LINE	SX 160	SX 220	SX 270	SX 320	SX 480	SX 570	SX 660
Processor	Dual-core Arm Cortex-A9 MPCore processor						
Maximum processor frequency	1.5 GHz <sup>1</sup>						
Processor cache and co-processors	<ul style="list-style-type: none"> <li>• L1 instruction cache (32 KB)</li> <li>• L1 data cache (32 KB)</li> <li>• Level 2 cache (512 KB) shared</li> <li>• FPU single and double precision</li> <li>• Arm Neon* media engine</li> <li>• Arm CoreSight* debug and trace technology</li> <li>• Snoop control unit (SCU)</li> <li>• Acceleration coherency port (ACP)</li> </ul>						
Scratch pad RAM	256 KB						
HPS DDR memory	DDR4 and DDR3 (Up to 64 bit with error correction code (ECC))						
Direct memory access (DMA) controller	8 channels						
EMAC	3X 10/100/1000 EMAC with integrated DMA						
USB OTG controller	2X USB OTG with integrated DMA						
UART controller	2X UART 16550 compatible						
Serial peripheral interface (SPI) controller	4X SPI						
I <sup>2</sup> C controller	5X I <sup>2</sup> C						
Quad SPI flash controller	1X SIO, DIO, QIO SPI flash supported						
SD/SDIO/MMC controller	1X eMMC 4.5 with DMA and CE-ATA support						
NAND flash controller	<ul style="list-style-type: none"> <li>• 1X ONFI 1.0 or later</li> <li>• 8 and 16 bit support</li> </ul>						
General-purpose timers	7X						
Software-programmable GPIOs	Maximum 54 GPIOs						
Direct shared I/Os	48 I/Os to connect HPS peripherals directly to I/O						
Watchdog timers	4X						
Security	Secure boot, Advanced Encryption System (AES), and secure hash algorithm						

Notes:

1. With overdrive feature.